

FAG N1034-K-M1-SP参数

| | | | | |
|--------|----------------------|--------|-------|-------------|
| 尺寸 | r_{\min} | 2.1 | mm | - |
| | s | 6 | mm | 距离中心位置的轴向偏移 |
| 重量 | m | 7770 | g | 质量 |
| 基本额定载荷 | C_r | 300000 | N | 基本额定动载荷，径向 |
| | C_{0r} | 430000 | N | 基本额定静载荷，径向 |
| 极限转速 | $n_{G \text{ Fett}}$ | 3600 | r/min | 脂润滑时的极限转速 |
| | $n_{G \text{ Öl}}$ | 0 | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | C_{ur} | 59000 | N | 疲劳极限载荷，径向 |
| 尺寸 | d | 170 | mm | - |
| | D | 260 | mm | - |
| | B | 42 | mm | - |
| | $D_{a \text{ max}}$ | 250 | mm | - |
| | $D_{b \text{ min}}$ | 239 | mm | - |
| | d_1 | 200.9 | mm | - |
| | $d_{a \text{ min}}$ | 180.5 | mm | - |
| | E | 237 | mm | - |
| | $r_{a \text{ max}}$ | 2.1 | mm | - |

FAG N1034-K-M1-SP图片



