

FAG 31312-A参数

尺寸	$d_a \text{ max}$	73	mm	-
	$d_b \text{ min}$	72	mm	-
	$r_{1, 2} \text{ min}$	3	mm	-
	$r_{3, 4} \text{ min}$	2.5	mm	-
	$r_a \text{ max}$	3	mm	-
	$r_b \text{ max}$	2.5	mm	-
重量	m	1940	g	质量
基本额定载荷	C_r	146000	N	基本额定动载荷, 径向
	C_{0r}	169000	N	基本额定静载荷, 径向
计算系数	e	0.83		-
	Y	0.73		-
	Y_0	0.4		-
疲劳极限载荷	C_{ur}	20200	N	疲劳极限载荷, 径向
极限转速	n_G	5400	r/min	极限转速
参考转速	n_B	3750	r/min	参考速度
说明		T7FB060		根据 DIN ISO 355 的 对应型号
尺寸	d	60	mm	-
	D	130	mm	-
	T	33.5	mm	-
	a	41	mm	-
	B	31	mm	-
	C	22	mm	-
	$C_a \text{ min}$	5	mm	-
	$C_b \text{ min}$	11.5	mm	-
	$D_a \text{ max}$	118	mm	-
	$D_a \text{ min}$	103	mm	-
	$D_b \text{ min}$	123	mm	-

FAG 31312-A图片

