

NSK 51212参数

| | | | | |
|--------|------|--------|-------|------|
| 外形尺寸 | T4 | 31 | mm | - |
| | SR | 1.0 | mm | (最小) |
| 基本额定载荷 | CAN | 71500 | N | 动载荷 |
| | COAN | 169000 | N | 静载荷 |
| | CA | 7300 | kgf | 动载荷 |
| | COA | 17200 | kgf | 静载荷 |
| 极限转速 | GRE | 2000 | 1/min | 脂润滑 |
| | OIL | 3000 | 1/min | 油润滑 |
| 尺寸 | SD1 | 95 | mm | - |
| | D1 | 62 | mm | - |
| | D2 | 78 | mm | - |
| | D3 | 100 | mm | - |
| | SB | 9.0 | mm | - |
| | A | 32.5 | mm | - |
| | R | 72 | mm | - |
| 安装尺寸 | SDA | 81 | mm | (最小) |
| | DA | 74 | mm | (最大) |
| | SRA | 1.0 | mm | (最大) |
| 重量 | MASS | 673 | g | 重量 |
| 型号 | 型号 | 51212 | | - |
| 外形尺寸 | SD | 60 | mm | 内径 |
| | D | 95 | mm | 外径 |
| | T | 26 | mm | 宽度 |
| | T3 | 28.0 | mm | - |

NSK 51212图片



参考资料:<http://www.sozhou.com/p/4202c144.html>

