

### INA GIKSR18-PS参数

尺寸	d	18	mm	轴承座孔径公差：H7 (算术平均值) 公差： +0,018 / 0
	d <sub>2 max</sub>	47	mm	-
	l <sub>4</sub>	94.5	mm	-
说明		0.005 - 0.045	mm	径向内部游隙
尺寸	B	23	mm	公差：0 / -0,12
	C <sub>1</sub>	16.5	mm	-
	D	35	mm	-
	d <sub>1</sub>	21.8	mm	-
	d <sub>3</sub>	M18x1.5		-
	d <sub>4</sub>	25	mm	-
	d <sub>5</sub>	31	mm	-
	d <sub>K</sub>	31.7	mm	-
	h <sub>1</sub>	71	mm	-
	l <sub>3 min</sub>	27	mm	-
	l <sub>5</sub>	10	mm	-
	l <sub>7 min</sub>	23	mm	-
	r <sub>1s min</sub>	0.3	mm	倒角尺寸
	W	27	mm	-
接触角	α	15		-
重量	m	295	g	质量
基本额定载荷	C <sub>r</sub>	47500	N	基本额定动载荷，径向
	C <sub>0r</sub>	23000	N	基本额定静载荷，径向 轴承座的基本额定载荷

### INA GIKSR18-PS图片

