

NSK 53336XU参数

| | | | | |
|------|--------|---------|--------|------|
| 尺寸 | A | 91.0 | mm | - |
| | R | 225 | mm | - |
| 安装尺寸 | SDA | 251 | mm | (最小) |
| | DA | 229 | mm | (最大) |
| | SRA | 2.5 | mm | (最大) |
| 重量 | MASS | 34900 | g | 重量 |
| 型号 | 型号 | 53336XU | | - |
| 外形尺寸 | SD | 180 | mm | 内径 |
| | D | 300 | mm | 外径 |
| | T | 95 | mm | 宽度 |
| | T3 | 99.3 | mm | - |
| | T4 | 109 | mm | - |
| | SR | 3.0 | mm | (最小) |
| | 基本额定载荷 | CAN | 480000 | N |
| COAN | | 1680000 | N | 静载荷 |
| CA | | 49000 | kgf | 动载荷 |
| COA | | 171000 | kgf | 静载荷 |
| 极限转速 | GRE | 560 | 1/min | 脂润滑 |
| | OIL | 850 | 1/min | 油润滑 |
| 尺寸 | SD1 | 295 | mm | - |
| | D1 | 184 | mm | - |
| | D2 | 240 | mm | - |
| | D3 | 310 | mm | - |
| | SB | 32.0 | mm | - |

NSK 53336XU图片



参考资料:<http://www.sozhou.com/p/c9081893.html>

