

## FAG 31309-A参数

尺寸	d	45	mm	-
	D	100	mm	-
	T	27.25	mm	-
	a	32	mm	-
	B	25	mm	-
	C	18	mm	-
	C <sub>a min</sub>	4	mm	-
	C <sub>b min</sub>	9	mm	-
	D <sub>a max</sub>	91	mm	-
	D <sub>a min</sub>	79	mm	-
	D <sub>b min</sub>	95	mm	-
	d <sub>1</sub>	75.8	mm	-
	d <sub>a max</sub>	56	mm	-
基本额定载荷	C <sub>0r</sub>	108000	N	基本额定静载荷，径向
计算系数	e	0.83		-
	Y	0.73		-
	Y <sub>0</sub>	0.4		-
疲劳极限载荷	C <sub>ur</sub>	12700	N	疲劳极限载荷，径向
极限转速	n <sub>G</sub>	7100	r/min	极限转速
参考转速	n <sub>B</sub>	4650	r/min	参考速度
说明		T7FB045		根据 DIN ISO 355 的 对应型号
尺寸	d <sub>b min</sub>	54	mm	-
	r <sub>1, 2 min</sub>	2	mm	-
	r <sub>3, 4 min</sub>	1.5	mm	-
	r <sub>a max</sub>	2	mm	-
	r <sub>b max</sub>	1.5	mm	-
重量	m	998	g	质量

FAG 31309-A图片

