

NSK 51332X参数

| | | | | |
|------|--------|---------|--------|------|
| 重量 | MASS | 19600 | g | 重量 |
| 型号 | 型号 | 51332X | | - |
| 外形尺寸 | SD | 160 | mm | 内径 |
| | D | 270 | mm | 外径 |
| | T | 87 | mm | 宽度 |
| | T3 | 91.7 | mm | - |
| | T4 | 100 | mm | - |
| | SR | 3.0 | mm | (最小) |
| | 基本额定载荷 | CAN | 475000 | N |
| COAN | | 1570000 | N | 静载荷 |
| CA | | 48500 | kgf | 动载荷 |
| COA | | 160000 | kgf | 静载荷 |
| 极限转速 | GRE | 600 | 1/min | 脂润滑 |
| | OIL | 900 | 1/min | 油润滑 |
| 尺寸 | SD1 | 265 | mm | - |
| | D1 | 164 | mm | - |
| | D2 | 215 | mm | - |
| | D3 | 280 | mm | - |
| | SB | 29.0 | mm | - |
| | A | 77.0 | mm | - |
| | R | 200 | mm | - |
| 安装尺寸 | SDA | 225 | mm | (最小) |
| | DA | 205 | mm | (最大) |
| | SRA | 2.5 | mm | (最大) |

NSK 51332X图片



参考资料:<http://www.sozhou.com/p/e7d7a4e1.html>

