

FAG 32921 参数

尺寸	d	105	mm	-	
	D	145	mm	-	
	T	25	mm	-	
	a	25	mm	-	
	B	25	mm	-	
	C	20	mm	-	
	$C_{a \text{ min}}$	5	mm	-	
	$C_{b \text{ min}}$	5	mm	-	
	$D_{a \text{ max}}$	136	mm	-	
	$D_{a \text{ min}}$	135	mm	-	
	$D_{b \text{ min}}$	140	mm	-	
	d_1	125	mm	-	
	$d_{a \text{ max}}$	114	mm	-	
	$d_{b \text{ min}}$	112	mm	-	
	$r_{1, 2 \text{ min}}$	1.5	mm	-	
	$r_{3, 4 \text{ min}}$	1.5	mm	-	
	$r_{a \text{ max}}$	1.5	mm	-	
	$r_{b \text{ max}}$	1.5	mm	-	
	重量	m	1150	g	质量
	基本额定载荷	C_r	128000	N	基本额定动载荷, 径向
C_{0r}		217000	N	基本额定静载荷, 径向	
计算系数	e	0.34		-	
	Y	1.75		-	
	Y_0	0.96		-	
疲劳极限载荷	C_{ur}	25500	N	疲劳极限载荷, 径向	
极限转速	n_G	4700	r/min	极限转速	
参考转速	n_B	2650	r/min	参考速度	

FAG 32921图片

